

用 途

4-79 型离心通风机可用于一般工厂及大型建筑物的室内通风换气，它既可用于输入气体，也可用来输出气体，输送气体的种类为空气或其他不自燃、不自爆、无缠绕性、对人体无害、对钢铁材料无腐蚀性之气体。气体内不许有粘性物质，所含尘土及硬质颗粒物不大于 150mg/m³。气体温度不得超 80℃，其它性能相近者亦可选用。

4-79 型离心通风机№3A、3.5A 性能与选用件表

机号	传动方式	转速 r/min	序号	出口风速 m/s	全压 Pa	流量 m³/h	电机		支脚螺栓（四套） 代号 F2120
							型号	功率 KW	
3	A	2900	1	7.2	1196	1970	Y90S-2 (B35)	1.5	M8×200
			2	8.0	1167	2180			
			3	8.5	1157	2430			
			4	9.6	1118	2670			
			5	10.2	1069	2900			
			6	11.0	1040	3130			
			7	12.3	892	3480			
			8	13.5	726	3830			
3	A	1450	1	3.5	304	990	Y802-4 (B35)	0.75	M8×200
			2	4.0	294	1100			
			3	4.5	284	1220			
			4	4.9	275	1340			
			5	5.3	265	1450			
			6	5.7	255	1560			
			7	6.4	226	1740			
			8	7.0	177	1910			
3.5	A	2900	1	8.4	1628	3120	Y100L-2 (B35)	3	M10×250
			2	9.3	1589	3460			
			3	10.3	1569	3860			
			4	11.4	1510	4240			
			5	12.3	1461	4600			
			6	13.3	1422	4960			
			7	14.8	1206	5520			
			8	16.3	981	6070			

3.5	A	1450	1	4.2	412	1560	Y90S-4 (B35)	1.1	M8×200
			2	4.7	402	1750			
			3	5.2	392	1930			
			4	5.7	382	2120			
			5	6.2	363	2300			
			6	6.7	353	2480			
			7	7.4	304	2760			
			8	8.2	245	3040			

4-79 型离心通风机№4A、4.5A 性能与选用件表

机号	传动方式	转速 r/min	序号	出口风速 m/s	全压 Pa	流量 m³/h	电机		支脚螺栓（四套） 代号 F2120
							型号	功率 KW	
4	A	2900	1	9.6	2138	4670	Y132S1-2(B35)	5.5	M10×250
			2	10.7	2079	5220			
			3	11.9	205	5760			
			4	13.0	01981	6310			
			5	14.1	1902	6860			
			6	15.2	1853	7410			
			7	16.9	1579	8240			
			8	18.6	1275	9080			
4	A	1450	1	4.8	530	2330	Y90S-4 (B35)	1.1	M8×200
			2	5.35	520	2610			
			3	5.9	510	2880			
			4	6.5	490	3160			
			5	7.0	481	3430			
			6	7.6	461	3710			
			7	8.5	392	4120			
			8	9.3	324	4540			
4.5	A	2900	1	100.8	2697	6640	Y160M1-2 (B35)	11	M10×250
			2	12.1	2628	7440			
			3	13.3	2999	8200			
			4	14.6	2511	8990			
			5	15.9	2412	9790			
			6	17.1	2344	10550			
			7	19.1	2001	11720			
			8	21.0	1618	12920			

4.5	A	1450	1	5.4	677	3320	Y90L-4 (B35)	1.5	M8×200
			2	6.0	657	3720			
			3	6.7	647	4110			
			4	7.3	628	4510			
			5	7.9	598	4890			
			6	8.6	8588	5270			
			7	9.5	500	5860			
			8	10.4	402	6450			

4-79 型离心通风机№5A、6A 性能与选用件表

机号	传动方式	转速 r/min	序号	出口风速 m/s	全压 Pa	流量 m³/h	电机		支脚螺栓（四套） 代号 F2120
							型号	功率 KW	
5	A	2900	1	12.0	3334	9100	Y160M2-2 (B35)	15	M12×320
			2	13.4	3256	10200			
			3	14.8	3217	11250			
			4	16.2	3099	12350			
			5	17.6	2981	13410			
			6	19.1	203	14480			
			7	21.2	2471	16100			
			8	23.3	2001	17720			
5	A	1450	1	6.0	834	4560	Y100L1-4 (B35)	2.2	M10×250
			2	6.7	814	5100			
			3	7.4	804	5630			
			4	8.1	775	6180			
			5	8.8	745	6710			
			6	9.1	726	7240			
			7	10.6	618	8050			
			8	11.7	500	8860			
6	A	1450	1	7.4	1196	7890	Y132S-4 (B35)	5.5	M10×250
			2	8.2	1177	8820			
			3	9.1	1157	9740			
			4	10.0	1118	10700			
			5	10.8	1069	11600			
			6	11.6	1040	12520			
			7	13.0	892	13920			
			8	14.3	706	15320			

6	A	960	1	4.9	530	5230	Y100L-6 (B35)	1.5	M10×250
			2	5.5	520	5840			
			3	6.0	51	6420			
			4	6.6	490	7080			
			5	7.2	471	7680			
			6	7.7	451	8290			
			7	8.6	402	9220			
			8	9.4	314	10100			

4-79 型离心通风机№7C 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
7	C	1800	1	2501	15580	Y180L-4	22	C	4	3658	65-C4-280	48-C4-355	3912-015
			2	2461	17400								
			3	2422	19200								
			4	2334	21100								
			5	2236	22860								
			6	2177	24700								
			7	1876	27600								
			8	1481	30200								
7	C	1600	1	1971	13850	Y160L-4	15	B	4	3353	65-B4-280	42-B4-315	3912-015
			2	1942	15450								
			3	1912	17100								
			4	1844	18750								
			5	1765	20300								
			6	1716	21950								
			7	1481	24500								
			8	1167	26850								
7	C	1250	1	1206	10820	Y132M-4	7.5	B	4	3353	65-B4-280	38-B4-250	3912-014
			2	1187	12120								
			3	1167	13340								
			4	1128	14650								
			5	1079	15850								
			6	1049	17150								
			7	902	19160								
			8	716	20850								

7	C	1120	1	971	9650	Y132S-4	5.5	B	4	3353	65-B4-280	38-B4-224	3912-014
			2	951	10830								
			3	932	11950								
			4	902	13100								
			5	863	14200								
			6	843	15350								
			7	726	17200								
			8	549	18800								

4-79 型离心通风机№7C 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
7	C	1000	1	775	8650	Y112M-4	4	B	4	3175	65-B4-280	28-B4-200	3912-014
			2	755	9660								
			3	745	10660								
			4	716	11700								
			5	686	12700								
			6	667	13700								
			7	578	15300								
			8	461	16800								
7	C	900	1	628	7780	Y100L2-4	3	A	2	3175	65-A2-280	280-A2-180	3912-014
			2	608	8690								
			3	598	9600								
			4	579	10500								
			5	559	11400								
			6	539	12300								
			7	471	13800								
			8	373	15100								
7	C	800	1	500	6920	Y100L1-4	2.2	A	2	3175	65-A2-280	28-A2-160	3912-014
			2	481	7730								
			3	471	8400								
			4	461	9360								
			5	441	10160								
			6	422	10970								
			7	373	12240								
			8	294	13440								

7	C	710	1	392	6110	Y90L-4	1.5	A	2	3175	65-A2-280	24-A2-140	3912-013
			2	382	6850								
			3	373	7560								
			4	363	8310								
			5	343	9020								
			6	333	9730								
			7	294	10870								
			8	235	11900								

4-79 型离心通风机№8C 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
8	C	1600	1	2491	21500	Y200L-4	30	C	4	3658	65-C4-280	55-C4-315	3912-015
			2	2452	24000								
			3	2422	26500								
			4	2334	29200								
			5	2236	31600								
			6	2177	34200								
			7	1873	38100								
			8	1481	41700								
8	C	1270	1	1569	17100	Y160L-4	15	B	4	3658	65-B4-280	42-B4-250	3912-015
			2	1549	19100								
			3	1530	21050								
			4	1471	23200								
			5	1412	25100								
			6	1373	27100								
			7	1177	30200								
			8	932	33100								
8	C	1120	1	1226	15050	Y160M-4	11	B	4	3658	65-B4-280	42-B4-224	3912-015
			2	1206	16800								
			3	1187	18550								
			4	1147	20400								
			5	1098	22100								
			6	1069	23900								
			7	922	26700								
			8	726	29200								

8	C	1000	1	971	13450	Y132M-4	7.5	B	4	3556	65-B4-280	38-B4-200	3912-014
			2	961	15000								
			3	951	16550								
			4	912	18500								
			5	873	19750								
			6	853	21400								
			7	735	23800								
			8	579	26050								

4-79 型离心通风机№8C 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
8	C	900	1	785	12100	Y132S-4	5.5	B	4	3556	65-B4-280	38-B4-180	3912-014
			2	775	13500								
			3	765	14900								
			4	735	16650								
			5	706	17800								
			6	686	19250								
			7	598	21400								
			8	471	23500								
8	C	800	1	618	10760	Y112M-4	4	B	4	3556	65-B4-280	28-B4-160	3912-014
			2	613	12000								
			3	608	13250								
			4	579	14800								
			5	559	15800								
			6	549	17130								
			7	471	19050								
			8	353	20850								
8	C	710	1	490	9520	Y100L2-4	3	A	2	3556	65-A2-280	28-A2-140	3912-014
			2	471	10660								
			3	466	11750								
			4	461	13140								
			5	441	14030								
			6	431	15200								
			7	373	16900								
			8	294	18800								

8	C	630	1	387	8450	Y112M-4	2. 2	A	2	3556	65-A2-280	28-A2-200	3912-014
			2	382	9460								
			3	378	10430								
			4	363	11670								
			5	343	12450								
			6	333	13500								
			7	294	15000								
			8	226	16450								

4-79 型离心通风机№10E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
10	E	1300	1	2609	38500	Y250M-4	55	D	5	4572	65-D5-380	65-D5-340	3912-020
			2	2560	44300								
			3	2393	50000								
			4	2226	55800								
			5	2001	59700								
			6	1775	63500								
10	E	1170	1	2118	34600	Y225S-4	37	D	5	4572	65-D5-380	60-D5-315	3912-018
			2	2079	39900								
			3	1942	45000								
			4	1804	50300								
			5	1618	53700								
			6	1442	57100								
10	E	1000	1	1540	29600	Y200L-4	22	C	4	4572	65-C4-380	48-C4-265	3912-015
			2	1510	34100								
			3	1412	38400								
			4	1314	42900								
			5	1177	45900								
			6	1049	48800								
10	E	940	1	1363	27850	Y180M-4	18.5	B	4	4521	65-B4-380	48-B4-250	3912-015
			2	1334	32050								
			3	1255	36100								
			4	1167	40300								

			5	1049	43200								
			6	932	45900								
10	E	830	1	1059	24550	Y160L-4	15	B	4	4521	65-B4-380	42-B4-224	3912-015
			2	1040	28300								
			3	971	31850								
			4	902	35600								
			5	814	38100								
			6	726	40500								

4-79 型离心通风机№10E、12E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
10	E	740	1	843	21900	Y160M-4	11	B	4	4521	65-B4-380	42-B4-200	3912-015
			2	823	25200								
			3	775	28400								
			4	716	31800								
			5	647	34000								
			6	579	36100								
10	E	660	1	667	19500	Y160M-6	7.5	B	4	4521	65-B4-380	42-B4-265	3912-015
			2	657	22500								
			3	618	25300								
			4	569	28300								
			5	510	30300								
			6	461	32200								
10	E	580	1	520	17160	Y132M2-6	5.5	B	4	4521	65-B4-380	38-B4-236	3912-014
			2	510	19800								
			3	471	22300								
			4	441	24900								
			5	392	26600								
			6	353	28300								
10	E	520	1	412	15400	Y132M1-6	4	B	4	4521	65-B4-380	38-B4-212	3912-014
			2	402	17700								
			3	382	19950								
			4	353	22300								

			5	314	23850								
			6	284	25400								
12	E	1040	1	2393	53300	Y280S-4	75	D	5	4572	65-D5-380	75-D5-270	3912-020
			2	2354	61300								
			3	2197	69100								
			4	2050	77100								
			5	1834	82600								
			6	1638	87800								

4-79 型离心通风机№12E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
12	E	940	1	1952	48200	Y250M-4	55	D	5	4572	65-D5-380	65-D5-250	3912-020
			2	1922	55400								
			3	1795	62400								
			4	1677	69600								
			5	1491	74600								
			6	1334	79300								
12	E	830	1	1530	42500	Y250M-6	37	D	4	4572	65-D5-380	65-D5-340	3912-020
			2	1500	48900								
			3	1402	55200								
			4	1304	61500								
			5	1167	65900								
			6	1040	70100								
12	E	740	1	1216	37900	Y200L2-6	22	C	4	4572	65-C4-380	55-C4-300	3912-018
			2	1196	43600								
			3	1108	49200								
			4	1040	54800								
			5	932	58700								
			6	824	62400								
12	E	660	1	961	33800	Y200L1-6	18.5	C	4	4572	65-C4-380	55-C4-265	3912-018
			2	951	38900								
			3	883	43800								
			4	824	48900								

			5	735	52400								
			6	657	55700								
12	E	580	1	755	29700	Y160L-6	11	B	4	4521	65-B4-380	42-B4-236	3912-015
			2	745	34200								
			3	686	38500								
			4	637	43000								
			5	569	46100								
			6	510	48900								

4-79 型离心通风机№12E、14E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
12	E	520	1	603	26650	Y160M-6	7.5	B	4	4521	65-B4-380	42-B4-212	3912-015
			2	598	30650								
			3	549	34500								
			4	510	38550								
			5	451	41300								
			6	402	43900								
12	E	470	1	490	24100	Y132M2-6	5.5	B	4	4521	65-B4-380	38-B4-190	3912-014
			2	485	27700								
			3	441	31200								
			4	412	34800								
			5	373	37300								
			6	333	39700								
12	E	420	1	387	21500	Y132M1-6	4	B	4	4521	65-B4-380	38-B4-170	3912-014
			2	382	24750								
			3	353	27900								
			4	333	31150								
			5	294	33400								
			6	265	35450								
14	E	830	1	2089	67400	Y315S-6	75	D	5	6096	90-D5-480	80-D5-410	SHT542-5
			2	2040	77500								
			3	1912	87600								
			4	1775	97700								

			5	1598	104400								
			6	1422	111000								
14	E	740	1	1657	60100	Y280M-6	55	D	5	5588	90-D5-480	75-D5-375	3912-020
			2	1618	69100								
			3	1520	78100								
			4	1412	87100								
			5	1265	92800								
			6	1128	98900								

4-79 型离心通风机№14E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
14	E	680	1	1402	55300	Y250M-6	37	D	5	5588	90-D5-480	65-D5-340	3912-020
			2	1373	63500								
			3	1285	71800								
			4	1187	80100								
			5	1069	85500								
			6	951	90900								
14	E	580	1	1020	47100	Y200L2-6	22	C	4	5588	90-C4-480	55-C4-300	3912-018
			2	990	54200								
			3	932	61200								
			4	863	68300								
			5	775	72700								
			6	686	77500								
14	E	520	1	814	42200	Y200L1-6	18.5	C	4	5334	90-C4-480	55-C4-265	3912-018
			2	794	48600								
			3	745	54900								
			4	696	61200								
			5	618	65300								
			6	549	69500								
14	E	460	1	637	37300	Y180L-6	15	C	4	5334	90-C4-480	48-C4-236	3912-015
			2	618	43000								
			3	579	48600								
			4	549	54000								

			5	481	57700								
			6	431	61500								
14	E	420	1	530	34050	Y160L-6	11	B	4	5334	90-B4-480	42-B4-212	3912-015
			2	510	39300								
			3	481	44300								
			4	461	49400								
			5	402	52700								
			6	363	56200								

4-79 型离心通风机№14E、16E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
14	E	370	1	412	30000	Y160M-6	7.5	B	4	5334	90-B4-480	42-B4-190	3912-015
			2	402	34600								
			3	373	39100								
			4	353	43500								
			5	314	46400								
			6	275	49400								
14	E	330	1	324	26800	Y132M2-6	5.5	B	4	5334	90-B4-480	38-B4-170	3912-014
			2	216	30850								
			3	294	34800								
			4	275	38800								
			5	245	41400								
			6	226	44100								
16	E	740	1	2177	89700	Y315M1-6	90	D	5	6858	90-D5-590	80-D5-455	SHT542-5
			2	2128	103200								
			3	1991	116600								
			4	1844	130100								
			5	1667	139100								
			6	1480	147800								
16	E	660	1	1726	80100	Y315S-6	75	D	5	6858	90-D5-590	80-D5-410	SHT542-5
			2	1687	92100								
			3	1589	104000								
			4	1432	116100								

			5	1324	124100								
			6	1177	131900								
16	E	580	1	1334	70300	Y280M-6	55	D	5	6858	90-D5-590	75-D5-355	3912-020
			2	1304	80900								
			3	1216	91400								
			4	1128	102000								
			5	1020	109100								
			6	902	11590								

4-79 型离心通风机№16E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
16	E	510	1	1030	61700	Y250M-6	37	D	5	6350	90-D5-590	65-D5-315	3912-020
			2	1010	71000								
			3	941	80300								
			4	873	89500								
			5	785	95700								
			6	696	101900								
16	E	470	1	873	56900	Y225M-6	30	C	4	6350	90-C4-590	60-C4-300	3912-018
			2	853	65600								
			3	804	74100								
			4	745	82600								
			5	667	88400								
			6	598	94000								
16	E	420	1	696	50800	Y200L1-6	18.5	C	4	6350	90-C4-590	55-C4-265	SHT542-3
			2	677	58600								
			3	637	66200								
			4	598	73800								
			5	530	79000								
			6	481	84000								
16	E	370	1	539	44800	Y180L-6	15	C	4	6350	90-C4-590	48-C4-236	SHT542-2
			2	530	51900								
			3	500	58400								
			4	461	65100								

			5	412	69600								
			6	373	74000								
16	E	330	1	431	40000	Y160L-6	11	B	4	6096	90-B4-590	42-B4-200	SHT542-2
			2	422	46100								
			3	392	52100								
			4	363	58000								
			5	324	62100								
			6	294	66100								

4-79 型离心通风机№16E、18E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
16	E	290	1	333	35100	Y160M-6	7.5	B	4	6096	90-B4-590	42-B4-230	SHT542-2
			2	324	40500								
			3	304	45700								
			4	284	51000								
			5	255	54500								
			6	226	58000								
18	E	660	1	2187	114000	Y315M2-6	110	D	7	7112	100-D7-640	80-D7-440	SHT542-5
			2	2138	131000								
			3	2010	148100								
			4	1844	165400								
			5	1677	176900								
			6	1491	187900								
18	E	580	1	1687	100200	Y315M1-8	75	D	5	7112	100-D7-640	80-D5-510	SHT542-5
			2	1648	115300								
			3	1549	130300								
			4	1422	145500								
			5	1294	155600								
			6	1147	165100								
18	E	520	1	1363	89900	Y315S-8	55	D	5	7112	100-D5-640	80-D5-475	SHT542-5
			2	1334	103400								
			3	1245	116900								
			4	1147	130500								

			5	1040	139200								
			6	932	148100								
18	E	470	1	1108	81200	Y280M-8	45	D	5	6858	100-D5-640	75-D5-410	SHT542-4
			2	1089	93400								
			3	1020	105500								
			4	932	117900								
			5	853	126000								
			6	755	133800								

4-79 型离心通风机№18E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
18	E	420	1	883	72500	Y250M-8	30	C	4	6858	100-C4-640	65-C4-370	SHT542-4
			2	863	83400								
			3	814	94200								
			4	745	105200								
			5	677	112600								
			6	598	119500								
18	E	370	1	686	63800	Y225M-8	22	C	4	6858	100-C4-640	60-C4-330	SHT542-3
			2	667	73500								
			3	628	84000								
			4	579	92600								
			5	530	99100								
			6	461	105400								
18	E	330	1	549	56900	Y200L-8	15	C	4	6858	100-C4-640	55-C4-300	SHT542-3
			2	530	65600								
			3	500	74900								
			4	461	82600								
			5	422	88400								
			6	363	94000								
18	E	290	1	422	50400	Y180L-8	11	B	4	6350	100-B4-640	48-B4-265	SHT542-2
			2	402	57600								
			3	382	65800								
			4	353	72600								

			5	324	77600								
			6	284	82600								
18	E	260	1	343	44800	Y160L-8	7. 5	B	4	6350	100-B4-640	42-B4-236	SHT542-2
			2	324	51700								
			3	304	59000								
			4	284	65100								
			5	255	69600								
			6	226	74100								

4-79 型离心通风机№20E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
20	E	580	1	2079	137500	Y355M1-8	132	D	7	7620	100-D7-740	90-D7-590	SHT542-7 SHT542-6
			2	2039	158400								
			3	1912	178700								
			4	1755	199700								
			5	1598	213500								
			6	1412	226500								
20	E	520	1	1677	123400	Y315M2-8	90	D	7	7620	100-D7-740	90-D7-530 80-D7-530	SHT542-7 SHT542-5
			2	1638	142000								
			3	1540	160200								
			4	1412	179000								
			5	1285	191300								
			6	1138	203000								
20	E	470	1	1373	111000	Y315M1-8	75	D	5	7112	100-D5-740	85-D5-470 80-D5-475	SHT542-6 SHT542-5
			2	1344	128300								
			3	1255	144800								
			4	1157	161700								
			5	1049	173000								
			6	932	183500								
20	E	420	1	1089	99600	Y315S-8	55	D	5	7112	100-D5-740	80-D5-425	SHT542-4
			2	1069	114800								
			3	1000	129400								
			4	922	144500								

			5	834	153900								
			6	745	163700								
20	E	370	1	843	87800	Y280S-8	37	D	5	7112	100-D5-740	75-D5-375	SHT542-4
			2	824	101200								
			3	775	114100								
			4	716	127400								
			5	647	135500								
			6	579	144100								

4-79 型离心通风机№20E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
20	E	330	1	677	78300	Y250M-8	30	C	4	6858	100-C4-740	65-C4-330	SHT542-4
			2	657	90400								
			3	618	101900								
			4	569	113700								
			5	510	120800								
			6	461	128600								
20	E	290	1	520	68800	Y225S-8	18.5	C	4	6858	100-C4-740	60-C4-300	SHT542-3
			2	510	79500								
			3	481	89500								
			4	441	100100								
			5	392	106100								
			6	353	11300								
20	E	260	1	422	61700	Y200L-8	15	B	4	6858	100-B4-740	55-B4-265	SHT542-3

			2	412	71200								
			3	382	80300								
			4	353	89600								
			5	314	95200								
			6	284	101400								

4-2×79 型离心通风机№5E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
5	E	2000	1	1607	13600	Y160M-4	11	B	4	3353	42-B4-280	42-B4-385	ST0201×02
			2	1568	14320								
			3	1539	15260								
			4	1519	15620								
			5	1480	16460								
			6	1450	17880								
			7	1372	18120								
			8	1206	18820								
5	E	1800	1	1382	9580	Y132M-4	7.5	B	4	3353	42-B4-280	38-B4-345	ST0201×02
			2	1362	9960								
			3	1343	11820								
			4	1274	13360								
			5	1235	14060								
			6	1196	14960								
			7	1147	15880								
			8	941	17160								
5	E	1550	1	1010	9620	Y132S-4	5.5	B	4	3353	42-B4-280	38-B4-300	ST0201×02
			2	980	10640								
			3	941	11560								
			4	892	12480								
			5	833	13310								
			6	794	13800								

			7	235	8630								
6	E	1800	1	1990	16760	Y180M-4	18.5	B	4	4521	42-B4-380	48-B4-470	ST0201×03
			2	1960	18780								
			3	1941	19340								
			4	1931	19520								
			5	1911	20800								
			6	1892	21900								
			7	1813	23200								
			8	1362	29820								

4-2×79 型离心通风机№6E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
6	E	1650	1	1676	15190	Y160L-4	15	B	4	3658	42-B4-280	42-B4-320	ST0201×03
			2	1647	17550								
			3	1627	18060								
			4	1617	18650								
			5	1598	19400								
			6	1568	20590								
			7	1529	21350								
			8	1186	27000								
6	E	1500	1	1392	13660	Y160M-4	11	B	4	3658	42-B4-280	42-B4-290	ST0201×03
			2	1353	15880								
			3	1333	17100								
			4	1323	17650								
			5	1304	18400								
			6	1274	19490								
			7	1225	20400								
			8	990	24550								
6	E	1400	1	1215	12890	Y160M-4	11	B	4	3658	42-B4-280	42-B4-270	ST0201×03
			2	1186	15040								
			3	1157	16330								
			4	1137	17190								
			5	1127	17400								
			6	1098	18190								

			7	1059	19190								
			8	814	23490								
6	E	1200	1	882	10990	Y132S-4	5.5	B	4	3556	42-B4-280	38-B4-230	ST0201×02
			2	853	14120								
			3	833	14910								
			4	813	15590								
			5	774	16880								
			6	725	17680								
			7	657	19340								
			8	588	20070								

4-2×79 型离心通风机№6E、7E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
6	E	1650	1	676	9610	Y112M-4	4	B	4	3556	42-B4-280	28-B4-200	ST0201×02
			2	637	13000								
			3	608	13590								
			4	588	14820								
			5	559	15470								
			6	510	16650								
			7	461	17560								
6	E	1500	1	500	8240	Y100L2-4	3	A	2	3556	42-A2-280	28-A2-170	ST0201×02
			2	461	11180								
			3	441	12240								
			4	422	13260								
			5	402	13490								
			6	363	14500								
			7	333	15050								
6	E	1400	1	392	7360	Y100L1-4	2.2	A	2	3556	42-A2-280	28-A2-150	ST0201×02
			2	382	8590								
			3	372	9780								
			4	362	10390								
			5	343	11210								
			6	314	12270								
			7	265	13380								
7	E	1200	1	1970	24930	Y200L-4	30	C	4	3658	48-C4-280	55-C4-315	ST0201×04

			2	1941	27810								
			3	1911	30780								
			4	1843	33750								
			5	1764	36540								
			6	1715	39510								
			7	1480	44100								
			8	1166	48330								

4-2×79 型离心通风机N₀7E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮 代号	电机槽轮 代号	电机导轨（两套） 代号
						型号	功率 KW	型号	根数	带长			
7	E	1250	1	1206	19470	Y160L-4	15	B	4	3658	48-B4-280	42-B4-250	ST0201×03
			2	1186	21810								
			3	1166	24010								
			4	1127	26370								
			5	1078	28530								
			6	1049	30870								
			7	902	34480								
			8	716	37710								
7	E	1120	1	970	17370	Y160M-4	11	B	4	3658	48-B4-280	42-B4-224	ST0201×03
			2	951	19490								
			3	931	21510								
			4	902	25380								
			5	863	25560								
			6	843	27630								
			7	725	30960								
			8	549	33840								
7	E	1000	1	774	15570	Y160M-4	11	B	4	3658	48-B4-280	42-B4-200	ST0201×03
			2	755	17380								
			3	745	19180								
			4	716	21060								
			5	686	22860								
			6	667	24660								

			7	578	27540								
			8	461	30240								
7	E	900	1	627	14000	Y132M-4	7.5	B	4	3556	48-B4-280	38-B4-180	ST0201×02
			2	608	15640								
			3	598	17280								
			4	578	18900								
			5	559	20520								
			6	539	22140								
			7	471	24840								
			8	473	27180								

4-2×79 型离心通风机№7E、8E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
7	E	800	1	500	12450	Y132S-4	5.5	B	4	3556	48-B4-280	38-B4-160	ST0201×02
			2	480	13910								
			3	471	15120								
			4	461	16840								
			5	441	18280								
			6	422	19740								
			7	372	22030								
			8	294	24190								
7	E	710	1	392	10990	Y100L2-4	3	A	2	3556	48-A2-280	28-A2-140	ST0201×02
			2	382	12330								
			3	372	13600								
			4	363	14950								
			5	343	16230								
			6	333	17510								
			7	294	19566								
			8	235	21420								
8	E	1270	1	1570	23760	Y200L-4	30	C	4	3658	48-C4-280	55-C4-250	ST0201×04
			2	1550	30560								
			3	1530	33680								
			4	1472	37120								
			5	1413	40160								
			6	1373	43360								

			3	1510	79800								
			4	1412	89800								
			5	1265	95800								
			6	1147	102600								
10	E	940	1	1363	55700	Y225S-4	37	D	5	4572	65-D5-380	60-D5-250	SHT542-3
			2	1334	64100								
			3	1255	72200								
			4	1167	80600								
			5	1049	86400								
			6	932	91800								

4-2×79 型离心通风机№10E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
10	E	830	1	1059	49100	Y200L-4	30	C	4	4572	65-C4-380	55-C4-212	SHT542-3
			2	1040	56600								
			3	971	63700								
			4	902	71200								
			5	814	76200								
			6	726	81000								
10	E	740	1	843	43800	Y180M-4	18.5	B	4	4521	65-B4-380	48-B4-200	SHT542-2
			2	824	50400								
			3	775	56800								
			4	716	63600								
			5	647	68000								
			6	579	72200								
10	E	660	1	667	39000	Y180L-6	15	B	4	4521	65-B4-380	48-B4-265	SHT542-2
			2	657	45000								
			3	618	50600								
			4	569	56600								
			5	510	60600								
			6	461	64400								
10	E	580	1	520	34320	Y160L-6	11	B	4	4521	65-B4-380	42-B4-236	SHT542-2
			2	510	39600								
			3	471	44600								
			4	441	49800								

			5	392	53200								
			6	353	56600								
10	E	520	1	412	30800	Y160M-6	7.5	B	4	4521	65-B4-380	42-B4-212	SHT542-1
			2	402	35400								
			3	382	39900								
			4	353	44600								
			5	314	47700								
			6	284	50800								

4-2×79 型离心通风机№12E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
12	E	1040	1	2393	106600	Y315M1-4	132	D	7	4572	65-D7-380	80-D7-270	SHT542-5
			2	2354	122600								
			3	2197	138200								
			4	2050	154200								
			5	1834	165200								
			6	1638	175600								
12	E	940	1	1952	96400	Y280M-4	90	D	5	4572	65-D5-380	75-D5-250	SHT542-4
			2	1922	110800								
			3	1795	124800								
			4	1677	139200								
			5	1491	149200								
			6	1334	158600								
12	E	830	1	1530	85000	Y315S-6	75	D	5	4572	65-D5-380	80-D5-340	SHT542-5
			2	1500	97800								
			3	1402	110400								
			4	1304	123000								
			5	1167	151800								
			6	1040	140200								
12	E	740	1	1216	75800	Y280M-6	55	D	5	4572	65-D5-380	75-D5-300	SHT542-4
			2	1196	67200								
			3	1108	98400								
			4	1040	109600								

			5	1667	278200								
			6	1481	295600								
16	E	660	1	1726	160200	Y315M3-6	132	D	7	6858	90-D7-590	80-D7-410	SHT542-5
			2	1687	184200								
			3	1589	208000								
			4	1461	232200								
			5	1324	248200								
			6	1177	263800								

4-2×79 型离心通风机№16E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
16	E	580	1	1334	140600	Y315M1-6	90	D	5	6858	90-D5-590	80-D5-355	SHT542-5
			2	1304	161800								
			3	1216	182800								
			4	1128	204000								
			5	1020	218200								
			6	902	231800								
16	E	510	1	1030	123400	Y315S-6	75	D	5	6350	90-D5-590	80-D5-316	SHT542-5
			2	1010	142000								
			3	941	160600								
			4	873	179000								
			5	785	191400								
			6	696	203800								
16	E	470	1	873	113800	Y280M-6	55	D	5	6350	90-D5-590	75-D5-300	SHT542-4 (3912-020)
			2	853	131200								
			3	804	148200								
			4	745	165200								
			5	667	176800								
			6	598	188000								
16	E	420	1	696	101600	Y250M-6	37	D	5	6350	90-D5-590	65-D5-270	SHT542-4 (3912-020)
			2	677	117200								
			3	637	132400								
			4	598	147600								

			5	1294	311200								
			6	1147	330200								
18	E	520	1	1363	179800	Y355M1-8	132	D	7	7112	100-D7-640	90-D7-475	SHT542-6
			2	1334	206800								
			3	1245	233800								
			4	1147	261000								
			5	1040	278400								
			6	932	296200								

4-2×79 型离心通风机№18E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m ³ /h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
18	E	470	1	1108	162400	Y315M2-8	90	D	7	6858	100-D7-640	80-D7-410	SHT542-6
			2	1089	186800								
			3	1020	211000								
			4	932	235800								
			5	853	252000								
			6	755	267600								
18	E	420	1	883	145000	Y315M1-8	75	D	5	6858	100-D5-640	80-D5-375	SHT542-5
			2	863	166800								
			3	814	188400								
			4	745	210400								
			5	677	225200								
			6	598	239000								
18	E	360	1	647	124200	Y280S-8	37	D	5	6858	100-D5-640	75-D5-315	SHT542-4
			2	628	143000								
			3	598	163400								
			4	549	180200								
			5	500	192800								
			6	431	205000								
18	E	330	1	549	113800	Y250M-8	30	C	4	6858	100-C4-640	65-C4-300	SHT542-4
			2	530	131200								
			3	500	149800								
			4	461	165200								

			5	1049	346000								
			6	932	367000								
20	E	420	1	1089	199200	Y315M2-8	90	D	7	7112	100-D7-740	80-D7-425	SHT542-5
			2	1069	229600								
			3	1000	258880								
			4	922	289000								
			5	834	307800								
			6	745	327400								

4-2×79 型离心通风机№20E 性能与选用件表

机号	传动方式	转速 r/min	序号	全压 Pa	流量 m³/h	电机		三角皮带			风机槽轮	电机槽轮	电机导轨（两套）
						型号	功率 KW	型号	根数	带长	代号	代号	代号
20	E	370	1	843	175600	Y315M1-8	75	D	5	7112	100-D5-740	80-D5-375	SHT542-5
			2	824	202400								
			3	775	228200								
			4	716	254800								
			5	647	270000								
			6	579	288200								
20	E	330	1	677	156600	Y315S-8	55	D	5	6858	100-D5-740	80-D5-340	SGT542-5
			2	657	180800								
			3	618	203800								
			4	569	227400								
			5	510	241600								
			6	461	257200								
20	E	290	1	520	137600	Y280S-8	37	D	5	6858	100-D5-740	75-D5-300	SHT542-4
			2	510	159000								
			3	481	179000								
			4	441	200200								

			5	392	212200								
			6	353	226000								
20	E	260	1	422	123400	Y250M-8	30	C	4	6858	100-C4-740	65-C4-265	SHT542-4
			2	412	142400								
			3	382	160600								
			4	353	179200								
			5	314	190400								
			6	284	202800								